


A	45mm FUTURA DOOR
B	TIMBER JAMB (40mm) NOTE : HEAD = 70mm TO ACCOMODATE TRANSOME CLOSER
C	TIMBER ARCHITRAVE - MUST OVERLAP WALL STRUCTURE BY 5mm MINIMUM
D	FIRE SEALS
E	STAINLESS STEEL SCREWS @ 400mm CENTRES, MINIMUM 40mm PENETRATION INTO WALL STRUCTURE
F	MAX. 10mm FITTING GAP TO BE FILLED WITH: F-A PR EXPANDING FOAM (E.G. SIKA BOOM) AND F-B INTUMESCENT MATERIAL (E.G. BOSS MASTIC) TO FILL FITTING VOID
G	TIMBER STUD

CORE	FUTURA
FRR	-/30/30 sm
STUD	TIMBER
JAMB "J"	DAJ1D-35
WALL TYPE EXAMPLES	GBTL30, GBTL30b, GBTL30c

Title: Door Jamb	Date: 12/01/2021	Drawn By: HM	
Drawing No: HDJ-P45-73	Revision: 1.0	Checked By: HM	
		Sheet No: 1 / 1	Size: A3

©Hallmark Group. For the installation of Hallmark doors only. Ph: 03 313 4754